MATTONI™

UNILOCK
TECH SHEET

THICKNESS 60MM

REGION CHICAGO



EDGE
ZERO EDGE DETAIL

UNILOCK Exclusive Technologies

ENDURACOLOR

APPLICATIONS

Note: Not all sizes are suitable for every application. Contact Unilock Representative for assistance.



Borders and Accents



Driveway

Patio & Walkway

COLORS

DARK CHARCOAL
FINISH: SMOOTH
PREMIER

STANDARD
60mm x 240mm x 60mm
2 3/8" x 9 1/2" x 2 3/8"

SABLE
FINISH: SMOOTH
PREMIER

STANDARD
60mm x 240mm x 60mm
2 3/8" x 9 1/2" x 2 3/8"

COCOA BROWN
FINISH: SMOOTH
PREMIER

STANDARD
60mm x 240mm x 60mm
2 3/8" x 9 1/2" x 2 3/8"

GRANITE FUSION
SRI = 29

FINISH: SMOOTH
PREMIER



STANDARD
60mm x 240mm x 60mm
2 3/8" x 9 1/2" x 2 3/8"

LAYING PATTERNS



LP MATTONI HB C



LP MATTONI DHB D



LP MATTONI RB A

TYPICAL CROSS SECTION

Note: Base, screed bed, infill aggregates and or reinforcements may vary based on project requirements or as specified by engineer.



Residential Use	Minimum Base Thickness
Walkway or Patio	6"(150mm) - 8" (200mm)
Driveway	8"(200mm) - 12" (300mm)
Other	Contact Unilock

PACKAGING

	STANDARD
UNIT THICKNESS (MM)	60
LAYERS PER BUNDLE	10
LBS PER BUNDLE	2,965.33
LBS PER LAYER	296.53

rates and application procedures. Always test a small area to make sure the results are as expected.

Sealers

- Product may be sealed for aesthetic or cleanliness reasons but it is not required
- Use any sealer approved for concrete pavers
- Select type for desired aesthetics
- Product must be cleaned before sealing
- Always read and follow manufacturer's application procedures
- Always test a small area to make sure the results are as expected

The Americans with Disabilities Act Accessibility Guidelines (ADAAG) provides measurable criteria to determine compliance, not individual product evaluation. Gaps, joints or openings, greater than ½" horizontal and ¼" vertical should be avoided as they can disrupt wheelchair maneuvering (United States Access Board – Guidelines and Standards).

Contact Unilock Representative for actual color samples and availability. Unilock reserves the right to change product information without notice.

PDF Generated February 20, 2025, 2:26 pm

UNILOCK